Automatic Power Supply for Camcorder/Camera

Description

This Universal Notebook power supply can be used for power supply for different cameras or camcorder. Via USB interface you can also charge USB devices, like MP3 player, mobile phones and similar products.

In delivery included are 8 different adapters, which are suitable for different cameras. Optional there are also other adapters and cables by Delock available, in order to charge your notebook or mobile phone directly.

Ref. 41291
EAN 4043619412914

Images

Specification

- Automatic recognition of voltage
- With LED indicator for voltage
- Input: AC100-240V ~ 1.75A 47-63Hz
- Output: Adapter: DC 4.2-24V 4A (max) 70W
  USB: 5V 1A (max) 5W
- Size (LxWxH): 110 x 52.2 x 25.5 mm

Package content
- Universal power supply
- AC charger cable
- 8 adapter, bag
- User Manual

Package
- Retail Box

© 2010 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

8 Adapter included:

Adapter *for:* *Camcorder* *or* *Camera*

No	Output Volt-age	Range Voltage	Output Current Max	Connectors spec.	Camcorder/Camera
D01	8.4V	8.0-8.8V	1.5A	FM50	**SONY** L15A,L15B,L10A,L100
D02	8.4V	8.0-8.8V	1.5A	FH70	**SONY** L25A,L25B,L20A,L200
D03	5V	4.7-5.3V	2A	4.0*1.7*10.7 mm	**SONY** AC-PS100, **CANON** PS500, **CASIO** 40J,50J, **FUJI** AC-5VN,5VS, **KODAK** KWS0525, **OLYMPUS** E-5AC,D-7AC, **PANASONIC** VSK0625, **MINOLTA** AC4A,AC5A, **NIKON** EH-61
D04	8.4V	8.0-8.8V	2A	4.0*1.7*10.7 mm	**NIKON** EH-55, **CANON** PS700(S1 IS, S2 IS, S3 IS), **PANASONIC** VSK0578,VSK0615, NOJEEJ00001
D05	8.4V	8.0-8.8V	2.5A	4.8*1.7*10.7 mm	**KODAK** KWS0725, **PANASONIC** VSK0725,AC7
D07	11V	10.5-11.5V	1A	3.5*1.35*10.7 mm	**JVC** AP-V10/12/13U, **PANASONIC** VSK0613
D08	8.4V	8.0-8.8V	2A	3.0*0.8*10.7 mm	**CANON** PS700(for 40MC,50MC), **SAMSUNG** AD-1608
D10	5.1V	4.8-5.4V	1.1A	AC5	**PANASONIC** DMW-AC5

Optional Adapter for different Netbook, Notebooks:
(Please note that this power supply support Max. 4A 70W)

No	Item No	Output Volt-age	Range Voltage	Output Current Max	Connectors spec.	Netbooks / Notebooks
A	65146	19V	18.1-19.9V	4.74A	4.8*1.7*10.7 mm	**HP/COMPAQ** 18.5V/2.7A,18.5V/3.5A; **DELTA** 19V/2.64A; **ASUS** 19V/2.64A; **NEC** 19V/2.64A
B	65147	15V	14.3-15.7V	5A	6.3*3.0*10.7 mm	**TOSHIBA** 15V/3A,15V/4A
C	65148	19V	18.1-19.9V	4.74A	5.5*2.1*10.7 mm	**ACER** 19V/3.16A,19V/3.42A; **LITEON** 19V/3.16A,19V/3.42A; **NEC** 19V/3.16A
D	65149	19V	18.1-19.9V	4.74A	5.5*2.5*10.7 mm	**DELL** 19V/3.16A,19V/3.42A; **TOSHIBA** 19V/3.16A,19V/3.42A; **ASUS** LS:20V/3.25A; **DELTA** 19V/2.64A.; **LITEON** 19V/3.16A,19V/3.42A; **NEC** 19V/2.64A,19V/3.16A; **GATEWAY** 19V/3.16A,19V/3.42A,19V/3.68A
E	65150	16V	15.2-16.8V	5A	5.5*2.5*10.7 mm	**IBM** 16V/2.2A,16V/3.36A,16V/3.5A
F	65151	19V	18.1-19.9V	4.74A	5.5*3.0*10.7 mm	**SAMSUNG** 19V/3.16A
G	65152	16V	15.2-16.8V	5A	6.0*4.3*10.7 mm	**SONY** 16V/3.42A,16V/3.75A,16V/4A; **FUJITSU** 16V/3.36A, 16V/3.75A
H	65153	19.5V	18.5-20.4V	4.62A	6.0*4.3*10.7 mm	**SONY** 19.5V/2.7A,19.5V/3A; **FUJITSU** 19V/3.16A
I	65120	19V	18.1-19.9V	4.74A	5.5*1.7*10.7 mm	**ACER** 19V/3.42A; **DELTA** 20V/3.5A
J	65121	19.5V	18.5-20.4V	4.62A	7.4*5.0*12.5 mm	**DELL** 19.5V/3.34A
K	65122	20V	19.0-21.0V	4.5A	7.3*7.4 mm	**DELL** 20V/3.5A
L	65123	22V	21.9-23.1V	4A	3.5*1.35*9.5 mm	**SHARP** 22V/1.8A, 22V/2.04A
M	65124	20V	19.0-21.0V	4.5A	7.9*12*9.5 mm	**IBM/LENOVO** 20V/3.25A
N	65157	24V	22.8-25.2V	2.7A	7.7*2.5*4.3 mm	**Apple** 24V/2.65A, 24V/2A, 24V/1.875A
O	65158	24V	22.8-25.2V	2.7A	9.5*3.5*4.0 mm	**Apple** 24V/2.65A, 24V/2A, 24V/1.875A
Q	65125	18.5V	17.6-19.4V	4.9A	7.4*5.0*12.5 mm	**HP/COMPAQ** 18.5V/3.5A
R	65126	12V	11.4-12.6V	5A	5.5*2.5*10.7 mm	**For Monitors** 12V 4A, 12V 3A
S	65131	14V	13.3-14.7V	5A	5.5*2.5*10.7 mm	**For Monitors** 14V 4A, 14V 3A
U	65127	9.5V	9.0-10.0V	5A	4.8*1.7*10.7 mm	**ASUS** 9.5V/2.315A
V	65133	12V	11.4-12.6V	5A	4.8*1.7*10.7 mm	**ASUS** 12V/3A